

Passenger Demand for a High-speed Network Across Europe

Tilo SCHUMANN¹

Summary

The article presents the results of research investigation aimed at assessment of the future demand for passenger transport realized by high speed (HS) trains of a new generation. The researchers created the theoretical network, basing on the following pre-assumptions: 1) running speed of the trains will be 400 km/h; 2) cities with more than 500 000 inhabitants should have the HS station in the city; 3) cities bigger than 200 000 inhabitants should have the access to HS station in less than 50 km; 4) cities with more than 80 000 people should have the distance to the nearest HS station shorter than 100 km.

All cities, counting more than 80 000 inhabitants, and many smaller cities, are included into the theoretical network, which is based on the NUTS-2 units.

Basing on basic economical factors, mobility of population, availability of competing transport modes, purchasing power etc. the researchers built a model of passengers flows along all entire HS network connections. Firstly, the data of 2010 were applied, and the results have been compared with the real data from Eurostat and UIC statistics, just for calibration of the model. Then three scenarios have been evaluated: 1) Europe 2025 (including HSL's under construction and proposed); 2) New Generation Train (NGT) Maximum Network; 3) NGT Recommended Network.

Impact of different factors, particularly the distribution of the country's population, on calculated HS traffic demand is discussed. The results of calculations the author compares with actual development plans in different countries. Special focus is applied for situation in Poland, considering the proposed construction of the „Y” high speed line, connections based on CMK line, and international links. The calculations executed on NGT network model proved that the biggest potential for future growth of high speed passenger transport in Eastern Europe may be predicted for Poland, Romania and Turkey.

Keywords: future demand, high-speed (HS) trains, network model

¹ Dipl.-Ing. Scientist, Deutsches Zentrum für Luft- und Raumfahrt, e-mail: Tilo.Schumann@dlr.de

1. Introduction

The Next Generation Train (NGT) is a research project for a new type of high speed train (Figure 1). It is developed by DLR (German Aerospace Center), in which 8 institutes with their specialised knowledge are involved. The train is designed for an operational speed of 400 km/h. Due to its light body structure and double-deck concept, it has lower specific energy consumption than a conventional high speed train [1]. The Institute for Transportation Systems develops operational concepts for the train.



Fig. 1. Design study of the NGT 400

2. Object and Background

The object of the study is to analyse the potential for a high speed network with a design speed of 400 km/h. Within the scope of the project the geography and the present and future rail networks of the western, northern, southern and middle European countries are modeled and an exemplary network is created in order to verify which effect this speed has on European traffic.

A first study was made for the major European relation from Paris to Vienna via Stuttgart and Munich [2]. This analysis revealed the feasibility of switching air transport to rail even for distances up to 1000 km. The NGT covers the way in fewer than 4 hours. Major differences between the European countries are revealed: In Germany more frequent stops create more benefit because of the distributed population. The average speed for the passengers with a direct journey decreases. However the speed for all passengers in the investigation area increases due to the enhanced accessibility to high speed rail.

3. Method for Traffic Modelling

For the investigation of the European potential, a network is created, which includes the cities, the train routes and frequencies between the modelled cities, the travel times and economic data. The distribution of the traffic demand is created

with an elementary gravity model, scaled with real data from Eurostat [3] and the UIC railway statistics [4]. For the assignment a train-route-based routing algorithm is used, in which interchanges have a negative influence. Thus the fastest route is not always the best option.

3.1. Network Model

The population coverage is validated with the total population of the NUTS-2 areas [5]. This area definition is used by the European Union and represents smaller federal states or parts of them in Germany, regions in France and Italy and cluster of counties in the UK. The aim is that the cities represent at least 20% of the total population of the NUTS-2 area. In most cases the percentage is much higher. All cities with 80 000 inhabitants and more and also lots of smaller towns are included. Furthermore towns at railway nodes are added, because there are necessary for the network anyway. The limitation to cities and towns follows the idea that the biggest part of the rail potential lies in cities and not in rural areas.

The rail network is represented by train routes. These are distinguished into high speed, intercity and regional train routes. Also bus and ferry connections are included, if there is no useful connection to the rail network and the feeder potential is important. A special form of intercity train was introduced as IC+. This is for the cases where the strict definition of high speed (considerably higher than 200 km/h) is not fulfilled, but the trains are faster than ordinary intercity trains.

The train route numbering and the train travel times are gathered from the Thomas Cook European Timetable 2010 [6]. Regular stop times are included in the travel time. Average access, egress and interchange times are defined for every city.

3.2. Distribution and Assignment

The gravity model consists of the population of the regarded city pair, the economic power (purchasing power standard per capita in €), the distance and average travel speed. The result is the annual number of rail passengers for every city pair combination. This value is validated with the Eurostat data, where the rail traffic is given in a matrix on the NUTS-2 level. Scaling factors adapt the calculated value. For some relations, especially international and in Eastern Europe, the Eurostat data is missing or the value is not plausible, then the data from the UIC statistics is used. Furthermore a flight factor is introduced, which reduces the value for very long journeys. This factor is necessary as the potential decreases not fast enough for journeys of 4 hours and longer. For these travel times air traffic remains the most attractive mode.

The assignment is based on a train-route oriented routing algorithm. The route with the lowest travel resistance is chosen. The travel resistance consists of access

time, travel times, interchange times and the egress time. The interchange time is scaled with a factor, so that a more comfortable route is preferred compared to a little faster route.

Only long distance traffic with distances of more than 50 km is included in the model. This includes longer journeys in so called „regional” trains, which for instance wouldn't occur in the long distance statistics in Germany.

The international traffic is calculated using country-pair scaling variables. The effort for a more detailed study would be too big. It can be stated, that the level of international rail traffic is very different. In eastern European countries even for very long journeys railway is used, so the flight factor has to be reduced. For Western European countries much more traffic volume is expected, but the demand is lower, for example between Germany and the Netherlands.

3.3. Scenarios

Four scenarios are calculated:

1. Europe 2010 (for calibration).
2. Europe 2025 (forecast with rail lines under construction or planned).
3. NGT Maximum Network.
4. NGT Recommended Network.

The NGT Recommended Network is the result of the analysis of the Maximum Network. Only high speed lines which generate 10 million new travellers per year or more are included. The number is a recognized value for high speed lines. A more detailed cost-benefit analysis would require much more effort.

4. Network Model for Europe (2010)

All western, southern, northern and middle European countries are regarded in the model. In the east the Baltic countries, Poland, Slovakia, Hungary, Romania, Bulgaria and Turkey are included. Not included are Iceland (low potential) and the eastern European countries of Russia, Belarus, Moldavia and the Ukraine (Figure 2). The following numbers define the model network:

1. 1904 cities and towns.
2. 237 Mio inhabitants included of total 525 Mio.
3. 120 000 km rail lines included of total 227 000 km.
4. Length of high speed route network: 18 400 km.
5. Length of intercity and IC+ route network: 66 100 km.
6. Length of regional train route network: 75 600 km.




Fig. 2. Rail Network for Europe 2010 (Red = High Speed, Violet = IC+, Orange = IC, Green = Regional Trains, Thickness = Service interval)

4.1. Focus on Poland

For Poland 97 cities and towns with a total population of 14,6 Mio are included, this is 38% of the total population. Most of the long distance traffic (EC, IC, EIC and TLK) is assigned as „IC” and shown in orange on the map (Figure 3). Almost all cities are connected to this network, only for a few had to be connected with regional trains. The fastest line is the CMK line from Warszawa to Krakow and Katowice. This line has a straight alignment and could therefore be upgraded to high speed in the future. The long distance traffic in 2010 consists of a large number of direct trains across the country. „Direct trains” means, that there is often no necessity to change the train, but there are only few trains a day following these specific routes. The interval is more intense on central axes like Warszawa – Lodz and Warszawa – Katowice (CMK line). Many (seat-wagon-) trains are running also during the night. The modelled network has a length of 8 600 km which is 44% of the total network. The model speed of the IC trains is 60 km/h and for regional trains (only few lines modelled) 38 km/h. These are lower values compared to Western Europe. A couple of larger cities are not connected to passenger rail services




Fig. 4. Population per City / Town

In the above section the modelled percentage of the total network was mentioned. In Figure 5 the highest value can be found in the Netherlands where almost the whole network has importance for the passenger transport. A high value means that there are not much secondary lines or in the model are many smaller towns included, which have to be connected to the network. The first meaning can be assigned to the UK, Ireland, Spain, Denmark, Estonia and Greece. The second one is the cause for the high value in Switzerland.




Fig. 5. Modelled part of the total rail network length

In Figure 6 and Figure 7 the average speed of the model train types is displayed. It is weighted with the train running performance (train-km), but not the traffic performance (Pkm). The fastest high speed train routes can be found in Spain. This includes only AVE trains, gauge-changing trains partially using high speed lines are assigned as IC+. Because of the Eurostar also Great Britain has a high value. The French value is lower because of the large proportion of old lines TGV trains are running on. The same reason causes the low average speed of the German ICE. Even there are few high-speed line sections, the speed standard in the Scandinavian countries of Sweden and Finland is very high. The reason amongst others is the low number of stops on very long distances. The speed level for IC

traffic moves around 80–100 km/h in Western Europe. Britain has a higher level because of the limitation of stops allowed by the high train density. France and Finland have a low rural population density which reduces the number of intermediate stops. The difficult topography of Norway reduced the average speed there. A lower speed level in the formerly Eastern Bloc countries can be determined. The level is extraordinary low in former Yugoslavia except Slovenia and Croatia and Albania (no trains assigned as IC).




Fig. 6. Average Speed of High Speed and IC+ network




Fig. 7. Average Speed of the IC network

5. Scenario 2010

Currently most of the railway passengers have a national destination. In Fig. 8 national traffic is displayed in blue, whereas international traffic in red.




Fig. 8. Passenger long distance traffic 2010 in Central Europe

The highest passenger numbers are obtained mainly on the core high speed network. These are the following lines (only voyages for 50 km and longer, both directions):

Country	Line	Passengers per day	International
France	Paris – Dijon / Lyon (TGV)	95 000	5%
Switzerland	Zürich – Olten	85 000	5%
Germany	Frankfurt – Mannheim	80 000	11%
Austria	Wien – St. Pölten	65 000	10%
Italy	Roma – Firenze	55 000	1%
UK	London – Rugby (West Coast Main Line)	50 000	5%
Netherlands	Utrecht – Eindhoven	45 000	1%
Belgium	Brussels – Halle	34 000	78%
Sweden	Stockholm – Katrineholm	25 000	2%
Poland	Warszawa – Grodzisk Mazowiecki	25 000	1%
Czech Rep.	Praha – Kolin	21 000	13%
Denmark	Copenhagen – Roskilde	15 500	6%
Spain	Madrid – Barcelona	15 000	2%

With 95 000 passengers a day the LGV line from Paris to the Southeast is the most used high speed line in Europe with a high train frequency of 4–5 minutes. The map clarifies the fact that international rail traffic stands on a low level in Europe.

The calibration of the international traffic shows the different significance in different parts of Europe. The biggest intensity is between the Czech Republic and Slovakia. The calibration factors are on a level which is stronger than e.g. the inner German rail transport. Additionally the flight factor has to be reduced, so the passengers use the railway despite the long travel times. The traffic between Austria and Germany is on the same level as the inner German. Very strong connections are also between Germany and Switzerland, France and Switzerland, France and Italy and France and Luxemburg. The flight factor has to be reduced especially between Austria and Italy, Czech Republic and Poland, Spain and Portugal. A possible explanation for this amongst others is an intensive usage of night trains. The level of international traffic in the model is low between Germany and the Netherlands, France and the Netherlands and the UK and France. Nevertheless the strongest international connection in Europe is the Eurostar between London and Paris / Brussels. However the population, economic power and the short distance leads to expectations of much more traffic than there currently is. This is approved by the passenger numbers: The Eurostar couldn't fulfil the expectations the first years of its existence [7].

The number of relations with at least one passenger per day per inhabitant can serve as a value for the complexity of the traffic. The more complex the traffic relations are the more difficult is it to offer a good high speed rail to major parts of the population. Germany has the most complex origin-destination arrangement (400 relations/Mio inhabitants). Britain has the secondmost complex traffic (225), followed by Italy (180), Switzerland (175). Less complex the traffic is in France (85), Poland (80) and Spain (50).

6. Scenario 2025

For 2025 a forecast has been made, which takes the realisation of all rail lines now under construction or planned lines as a basis (Figure 9). Important new or upgraded line projects are amongst others:

- Germany: Leipzig – Erfurt – Nürnberg, Stuttgart – Ulm,
- Austria: Western Corridor, Koralm Corridor,
- Switzerland: Gotthard Base Tunnel,
- UK: High Speed 2 (London – Rugeley),
- France: LGVs: Bretagne, Bordeaux, Toulouse, Rhin-Rhone, Mediterranean,
- Spain: all major cities in coastal areas connected with Madrid,

- Italy: Milano – Venezia,
- Sweden: Stockholm – Malmö (partially),
- Poland: CMK Line (Warszawa – Krakow/Katowice),
- Turkey: Istanbul / Bursa – Ankara, Izmir – Ankara, Ankara – Sivas.




Fig. 9. Passenger long distance traffic in 2025

With the realisation of these projects the sum of the national traffic performance rises from 227 bn. Pkm in 2010 to 257 bn. Pkm in 2025. The passenger numbers rise from 909 to 986 Mio. The international traffic performance rises from 20 to 27 bn. Pkm, passenger numbers from 48 to 61 Mio.

The biggest increase is realised in Spain. The performance rises about 50% from 10,4 to 15,7 bn. Pkm. Even more new passengers can be attained in Turkey. The high speed lines revolutionize the passenger rail transport in Turkey. The performance rises from 2,4 to 10,7 bn. Pkm, passenger numbers from 9,5 to 30,6 Mio. Further high increases are calculated for Austria (+16%), France (+14%) and Greece (+25%), if the new sections of the Athens-Thessaloniki line are finished.

The biggest increase of the performance for international traffic is realised between Spain and France (+1300 Mio Pkm), Switzerland and France (+880 Mio Pkm), Switzerland and Germany (+572 Mio Pkm), France and Italy (+395 Mio Pkm) and Germany and Italy (+229 Mio Pkm).

7. Scenario NGT Maximum Network

The initial question for this work package of the NGT project was to identify the potential for a train with an operational speed of 400 km/h in Europe. The approach is to create a complete new network which allows railway operation at this high speed for almost the whole line. The existing network acts as a feeder network.

7.1. Network Development

To create this new network, strict rules are followed. These rules help to set the same scale to all regions of Europe regardless of the topography or established traffic corridors. The first rule classifies the cities. All cities with more than 500 000 inhabitants should have a direct connection to the network, for cities from 200 000 the high speed station should not be farther than 50 km away and for all cities from 80 000 inhabitants not farther than 100 km. The network itself follows some rules: parallel lines should have a distance of at least 100 km, the distance between stopping stations should be at least 50 km, the detour factor should not exceed 1,5. The lines should be connected with the existing central stations in the city center to avoid the increase of access and egress times. The operational speed within the city borders is reduced to allow the usage of the existing lines. In addition to the urban slow zones the travel time was increased by a factor to consider the exceeded line length which will occur in the detailed planning. Therefore the maximum network includes not the shortest theoretical travel times. The resulting network is shown in Figure 10, 11.

The maximum network is 77 000 km long and has 434 stations. Three longer subsea tunnels are investigated: under the Irish Sea from Holyhead to Dublin under the Baltic Sea from Stockholm to Turku and from Helsinki to Tallinn. The tunnel under the Fehmarn Strait is already included in the 2025 scenario.

The traffic performance would increase from 285 to 678 bn. Pkm. The part of the international traffic would rise from 11% to 37%. Countries with an extraordinary growth of national rail traffic are Poland (to 39 bn. Pkm, +218%), Romania (to 15 bn. Pkm, +536%) and Turkey (to 37 bn. Pkm, +251%). These countries have a big potential, founded by an optimal size and a number of big cities spread




Fig. 10. NGT Maximum Network




Fig. 11. Development of the international rail traffic from 2025 (left) to NGT Maximum scenario

over the country. Among the western European countries Germany would take the first place with 91 bn. Pkm heeling France (78 bn. Pkm). This figure shows that there is much undeveloped potential for high speed in Germany. The relative growth in France would be lower than in other countries due to the well developed high speed network in 2025. The same situation can be found in Spain. Smaller countries have low benefit with high speed lines, so the growth rates are low for example in Switzerland, then Netherlands, Belgium and Denmark.

The most important international connections develop between Austria and Germany (25 bn. Pkm), France and Italy (17 bn. Pkm) and Germany and Italy (11 bn. Pkm). Even long distances are rail-relevant so the connection Spain – Italy (8 bn. Pkm) and Spain – Germany (3 bn. Pkm).

7.2. Focus on Poland

In Poland there is a big potential for high speed lines because of the optimal size of the country and the existence of big cities in many parts of the country. Figure 12 shows the effect on passenger demand of the NGT Maximum Network compared to 2010. Only some of these lines are recommended and generate more than 10 Mio passengers a year (>25 000 passengers / day).




Fig. 12. Differential plot for passenger demand between 2010 and the NGT Maximum Network (green / light green = increase of demand, red / orange = decrease)

The center of the network emerges in Lodz. The planned Y-Line can be recognised, although it was not forced in the study. The line from Warszawa to Lodz will see 58 000 passengers / day, which could rise to 73 000 if only the Recommended Network will be taken as basis. Then there will be no direct line from Warszawa to Radom / Krakow. The advantage of creating a new line from Lodz

to Katowice via Czestochowa instead of using the CMK line is the integration of Lodz into the traffic between South Poland and Warszawa / Western Poland. This line faces a demand of 47 000 passengers / day, with the Recommended Network even 65 000. In the latter case the benefit of the line rises, because all traffic from South Poland to Warszawa and Poznan is routed via Lodz. The option of using the CMK line and creating a connection to Lodz from the South was not investigated, but could be alternatively a reasonable solution.

The Southern line from Katowice to Wroclaw is recommended. The extension to Zielona Gora is only recommendable together with the international connection to Germany. The lines from Poznan to Gorzow / Szczecin, Warszawa / Poznan to Gdansk and Warszawa to Bydgoszcz are possibly recommendable because they only create around 20–25 000 additional passengers / day. Disregarding the mentioned rules from above some towns along the recommended lines could be connected to increase the benefit-cost-ratio, e.g. Wloclawek, Kalisz, Legnica, Lubin, Glogow and Stargard Szczecinski.

One international connection is proposed: From Cottbus to Zielona Gora. This line will carry not only traffic from inner parts of Germany to Poland, but also the Berlin – Warszawa relation. The advantage is the combination of national and international traffic on most parts of the route both in Poland and Germany. In Germany the line is also used for the traffic Berlin – Dresden / Praha. The line from (Warszawa – Gorzow to Berlin had not enough potential on its own (14 000 passengers / day) and the decision was made to concentrate all traffic on the southern line. Alternatively also the existing line via Frankfurt / Oder could be upgraded.

Many lines of the Maximum scenario are not recommendable due to low patronage including the connection of Koszalin, Bialystok, Lublin, Rzeszow, Nowy Sacz and Walbrzych. Some old lines will of course experience a decrease of demand. These are the lines Warszawa – Poznan – Szczecin, Warszawa – Gdansk and the CMK line. The released capacity could be used for freight services.

8. Scenario NGT Recommendable Network

The maximum scenario remains theoretical because most of the lines have no national economic benefit exceeding the effort (Figure 13, 14). Even the operations would not be profitable on most lines. A detailed cost-benefit analysis would go beyond the scope of this work. But it is possible to calculate the attained passengers per line section. The loss on the old lines has to be taken in account. So this analysis is neither a cost-benefit analysis nor it takes capacity effects for instance for freight traffic into account.




Fig. 13. Recommendable NGT Network (dark blue = high probability for good benefit-cost-value, light blue = to investigate)




Fig. 14. Passenger long distance traffic on the NGT Recommendable Network

For high speed lines a number of 10 Mio new passengers per year on the line profile is said to fulfil the economic requirements to generate benefit [8]. The whole maximum network was analysed. The result is a network of 13 500 km, which is recommendable and further 9 000 km which have to be analysed deeper to come to a substantiated recommendation.

To have a look at the three subsea tunnels: Only the tunnel under the Irish Sea has potential (22 000 passengers / day). The Baltic tunnels have a too low demand (1000 passengers / day). Most of the recommended network is placed in Germany. Apart from the unused national potential an explanation is the central location with a noteworthy value of transit traffic. Exemplary connections are Benelux – Austria or France / Benelux – Poland / Czech Republic.

In France and Italy the recommended network consists basically of additional lines to the existing core network. With the exception of the Paris – Lyon line, which has extraordinary demand (150 000 passengers / day), these are lines along the Atlantic coast or through Central France and in Italy connections of Genova. In Britain connections to Scotland and around London are recommendable. A second channel tunnel with 400 km/h could increase the demand from 28 000 to 50 000 passengers a day. In the Czech Republic only international connections generate enough benefit to connect also national destinations to Prague. A lot of profitable lines seems to exist in Poland. The recommendable networks for Hungary and Romania have the design of a star with the capital as the origin. In Turkey a new line from Ankara to Istanbul would generate much more traffic than the high speed line under construction now. Also a connection from Istanbul to Izmir generates high benefit. It is noticeable that there are no recommendable lines in Spain. The network of 2025 is that much expanded that all the rail potential is captured and enhancement of the speed to 400 km/h does not have a significant effect.

9. Conclusions

In the context of the project Next Generation Train (NGT) of the German Aerospace Center (DLR) the potential for a European-wide high speed network for 400 km/h was calculated. The traffic model was calibrated with origin-destination data from Eurostat. The result is a recommendable network, in which the lines can reach a positive benefit-cost-value. The largest increase of traffic volume is realised in Central Europe, but also in Poland, Romania and Turkey. The international rail connections would grow most: the traffic performance increases by factor 7.

List of references

1. Winter et.al.: *Systematic derivation of the NGT rail vehicle concept*, RTR Special – NGT, 2011.
2. Schumann T.: *Operational concept Paris to Vienna*, RTR Special – NGT, 2011.
3. Eurostat Homepage, *Regional statistic on rail passengers*, tran_r_rapa, Origin-Destination matrices for 2005, <http://epp.eurostat.ec.europa.eu/portal/page/portal/transport/data/database>.
4. UIC, International Railway statistics, synopsis for 2009.
5. Eurostat, Statistical Regios: *Nomenclature des unités territoriales statistiques*, http://epp.eurostat.ec.europa.eu/portal/page/portal/nuts_nomenclature/introduction.
6. Thomas Cook European Rail Timetable, July/August 2010.
7. Eurostar Passenger Volume Development, UK Parliament 2006, <http://www.publications.parliament.uk/pa/cm200506/cmselect/cmpublic/727/72705.htm>.
8. Quote from Günter Ellwanger, former UIC High Speed Director.

Zapotrzebowanie na przewozy pasażerskie dla pociągów dużej prędkości

Streszczenie

Artykuł przedstawia wyniki badań nad oszacowaniem przyszłego zapotrzebowania na przewozy pasażerskie wykonywane pociągami dużej prędkości nowej generacji (NGT). Badacze stworzyli teoretyczną sieć połączeń, przyjmując następujące założenia: 1) prędkość kursowania pociągów rzędu 400 km/h; 2) miasta o liczbie ludności ponad 500 000 powinny mieć stację zlokalizowaną na sieci NGT; 3) miasta większe niż 200 000 mieszkańców powinny mieć dostęp do stacji NGT nie dłuższy niż 50 km; 4) miasta liczące ponad 80 000 ludności powinny mieć stację NGT w zasięgu do 100 km. Sieć teoretyczna uwzględniająca jednostki NUTS-2 objęła wszystkie europejskie miasta liczące ponad 80 000 mieszkańców, a także wiele mniejszych.

Model obliczeniowy opracowano z uwzględnieniem czynników gospodarczych, mobilności społecznej, dostępności konkurencyjnych środków transportu, siły nabywczej ludności itp. Obliczenia wykonano dla wszystkich połączeń wewnętrznych sieci modelowej. W pierwszej kolejności wprowadzono dane z 2010 roku, a wyniki porównano z danymi statystycznymi Eurostatu i UIC celem kalibracji modelu. Następnie wykonano obliczenia dla trzech scenariuszy: 1) Europa 2025 (z uwzględnieniem linii dużych prędkości w budowie i proponowanych); 2) sieć maksymalna NGT; 3) sieć rekomendowana NGT.

W artykule przedyskutowano wpływ różnych czynników, w szczególności rozkładu zaludnienia kraju, na popyt na przewozy pasażerskie pociągami dużej prędkości. Wyniki obliczeń porównano z planami rozwojowymi w różnych krajach. Specjalną uwagę zwrócono na wyniki obliczeń dla obszaru Polski, odnosząc się do proponowanej linii „Y”, połączeń przez linię CMK oraz relacji międzynarodowych. Wyniki obliczeń wykazują, że w Europie wschodniej największy potencjał wzrostu przewozu pasażerów kolejami dużej prędkości może być przewidywany dla Polski, Rumunii i Turcji.

Słowa kluczowe: zapotrzebowanie, przyszłość, pociągi dużej prędkości, model sieci

Спрос на будущие пассажирские перевозки для высокоскоростных поездов

Резюме

В данной статье представлены результаты исследований направленных оценить будущий спрос на пассажирские высокоскоростные поезда нового поколения (NGT). Исследователи создали теоретическую сеть, полагаясь на следующих допущениях: 1) скорость поездов 400 км / ч; 2) город, имеющий население более 500 000 – NGT должны иметь станции, расположенной в сети NGT; 3) город больше, чем 200 000 жителей должны иметь к станции NGT не больше чем 50 км; 4) города по 80 000 населения должны иметь станции NGT в пределах 100 км.

Сеть для теоретического исследования модели было построено на основе лиц NUTS-2 и охватывает все европейские города с более чем 80 000 жителей, а также множество мелких.

Расчетная модель была разработана с учетом экономических подвижных и социальных факторов, доступности конкурирующих видов транспорта, покупательной способности людей и других.

Результаты расчетов показывают, что в Восточной Европе наибольший потенциал для роста пассажирского высокоскоростного транспорта можно ожидать для Польши, Румынии и Турции.

Ключевые слова: будущий спрос, высокоскоростные поезда нового поколения, сетевая модель